

# LKF3/8" (R)

## 无线通信皱纹铜管 RF 电缆



### 结构参数

#### Construction Specification

	材料 Material	直径 Diameter(mm)
1.内导体 Inner Conductor	铜包铝线或铜线 Copper Clad Aluminum Wire or Copper	3.3
2.绝缘体 Dielectric	发泡聚乙烯 Foam PE	8.3
3.外导体 Outer Conductor	轧纹铜管 Corrugated Copper Tube	9.6
4.护套 Jacket	聚乙烯或低烟无卤防火聚乙烯 PE or Low Smoke Halogen-free Fire-retardant PE	11.2

### 电性能参数&机械性能及环境参数

#### Electrical Characteristics & Mechanical and Environmental Characteristics

阻抗 Impedance(Ohm)		50
电容 Capacitance(pF/m)		76
速率 Velocity(%)		88
峰值功率 Peak Power Rating(KW)		15.6
RF 峰值电压 RF Peak Voltage(KV)		1.05
绝缘阻抗 Insulation Resistance(M Ω .km)		>5000
截止频率 Cut-off Frequency(GHz)		13.5
绝缘电压 Insulation Voltage(KV)		2.5
内导体直流电阻 Inner Conductor DC Resistance( Ω /km)		3.10
外导体直流电阻 Outer Conductor DC Resistance( Ω /km)		2.80
护套电压 Jacket Spark(KV)		5.0
屏蔽衰减 Shielding Effectiveness(dB)		>120
驻波比 ≤ (回波损耗 ≥ dB) VSWR ≤ (Return loss ≥ dB)	0.005—3GHz	1.15 (23)
	0.8—1.0GHz	1.10 (26)
	1.7—2.0GHz	1.10 (26)
	2.0—2.4GHz	1.10 (26)
最小单次弯曲半径 Min. Single Bending Radius(mm)		40
最小多次弯曲半径 Min. Repeated Bending Radius(mm)		95
弯曲次数 No. of Bends		15
抗拉强度 Tensile Strength(kg)		53

贮存温度 Storage Temp.(°C)	-55~+85
安装温度 Installation Temp.(°C)	-40~+60
工作温度 Operating Temp.(°C)	-55~+85

**衰减(驻波比 1.0, 电缆温度 20°C)及平均功率(驻波比 1.0, 环境温度 40°C)**

**Attenuation(VSWR1.0,cable temp.20°C)and Average Power( VSWR1.0,ambient temp.40°C)**

频率 Frequency(MHz)	衰减 Attenuation(dB/100m)	平均功率 Average Power(KW)
100	3.12	2.23
200	4.45	1.56
450	6.79	1.02
800	9.20	0.75
900	9.80	0.71
1000	10.37	0.67
1500	12.90	0.53
1800	14.25	0.48
2000	15.10	0.46
2200	15.90	0.43
2400	16.70	0.42
2500	17.08	0.41
3000	18.90	0.37